

METAL PLATE  
EMBOSSER

**MATICA**  
TECHNOLOGIES



C320





# C320

## METAL PLATE EMOSSER

Model C320 has been specifically designed to provide low to medium volume metal marking applications with an electronic solution where, until today, the only low-cost alternatives have been manual systems. The C320, while ideal for industrial applications that require lower processing speed the one offered by more expensive systems or as a back-up unit for larger systems, still offers the convenience of an automatic plate feeder mechanism and on-line capability.

### COMPACT AND STURDY DESIGN

The design of the C320 is not only compact and ergonomic, thus allowing it to fit into any office or factory environment, but also sturdy and resistant. The cover, made in a combination of aluminium and self-extinguishable plastic material, allows the C320 to withstand harsh industrial environments thus ensuring its perfect functioning over time.

### QUIET OPERATION

The C320 features a silent embossing mechanism can therefore be placed in any industrial or office environment without disturbing employees.

### VARIABLE PLATE & FONT SIZE

The C320 is equipped with an automatic loading hopper and finished plates are ejected through a side slot. The C320 can be configured for either embossing or indent applications, using a wide choice of type styles, and the operator can manually adjust the machine for varying plate dimensions.

### ON LINE OR OFF LINE

Data entry can either be performed through the supplied keyboard or via PC or host using the optional RS232 interface. The C320 incorporates the Xon Xoff protocol and can easily be connected to any PC or host environment. The MatiCard® 3 Windows based software provides user-friendly interface between the operator and the model C320.

## TECHNICAL SPECIFICATIONS

### Productivity (45 ch/plate)

- Up to 80 plates/hour
- Recommended operating time: 4 hours/day (max 1 hour continuously + 15 minutes rest)

### Plate Handling

- Universal plate feeder
- Input hopper capacity: 200 plates (0.5 mm thickness)
- Side Eject
- Universal Clamp Holder

### Plate Personalization

- Minimum plate dimensions (L x W): 30.5 mm x 20.3 mm
- Maximum plate dimensions (L x W): 89 mm x 56 mm
- Maximum embossing area (L x W): 82 mm x 56 mm
- Maximum plate thickness:
- Stainless (350 & 328 only): 0.4 mm
- Aluminium (type styles 350 & 328): 0.5 mm
- Aluminium (type style 488): 0.4 mm
- Aluminium (type style 489): 0.9 mm

### Embossing Drum Configuration

- Embossing drum: 60 characters
- Standard type (alphanumeric): Simplex 2 (350) - 3 mm emboss
- Optional type (alphanumeric):
- USA Block (490)
- 0.40 mm emboss; Simplex 3 (489) 4 mm indent
- Elite dog tag (328) - 3 mm deboss

### Memory & Data

- Storable formats: 10
- Data format: 15 fields for 32 characters ea.
- Back-up battery: lithium

### Communication Interface

- Communication interface: RS232 serial port
- Protocol: Xon/Xoff

### Software

- Maticard 3 for Windows® (XP/7/8), Diagnostic and setup software

### Other Features

- Key-lock security feature
- LCD display (40 x 2) + 3 function keys
- PC keyboard
- Upgradeable firmware: via PC on Flash EPROM

### Dimensions & Weight

- L x W x H: 65 x 49 x 26 cm, Weight: 34 kg

### Electrical Requirements

- Power supply: 100 to 240 VAC (+/- 10%); 50/60 Hz (+/- 3 Hz)